

**ARIS GOLD CORPORATION**  
**JUBY PROJECT**



**Drill Results Summary Table – December 7, 2021**

Hole number	Intersection #	From (m)	To (m)	Downhole length (m)	True thickness (m)	Au g/t
GL21-45	1	67.0	72.8	5.8	4.4	2.17
GL21-45	2	88.8	94.0	5.2	3.9	0.68
GL21-45	3	100.0	120.0	20.0	15.2	0.46
GL21-45	4	142.2	175.0	32.9	25.1	0.99
GL21-45	5	181.0	208.0	27.0	20.7	1.42
GL21-46	1	94.0	97.0	3.0	2.4	0.75
GL21-46	2	117.0	138.2	21.2	17.2	0.43
GL21-46	3	177.0	184.0	7.0	5.7	5.74
GL21-46	4	223.5	251.5	28.0	23.1	0.83
GL21-47	1	10.5	13.5	3.0	2.3	0.50
GL21-47	2	21.0	28.5	7.5	5.7	0.68
GL21-47	3	57.0	67.5	10.5	8.0	0.60
GL21-47	4	74.4	145.3	70.9	54.5	1.18
GL21-47	5	155.8	159.5	3.7	2.8	1.74
GL21-47	6	201.5	214.0	12.6	9.7	4.75
GL21-47	7	225.0	231.6	6.6	5.1	1.05
GL21-48	1	45.8	74.0	28.2	21.5	0.79
GL21-48	2	83.0	141.0	58.0	44.6	0.90
GL21-48	3	172.0	180.1	8.1	6.2	0.79
GL21-48	4	188.6	203.9	15.3	11.9	2.48
GL21-49	1	39.4	43.9	4.5	3.5	2.64
GL21-49	2	90.2	94.5	4.4	3.4	0.97
GL21-50	1	92.0	106.5	14.5	10.8	1.11
GL21-51	1	63.0	68.3	5.3	4.3	0.50
GL21-52	1	54.0	57.0	3.0	2.3	1.53
GL21-52	2	111.0	125.1	14.1	10.9	2.30
GL21-53	1	69.8	72.8	3.0	2.2	0.76
GL21-54	1	67.0	70.0	3.0	2.4	0.44
GL21-54	2	135.0	137.9	2.9	2.3	1.12
GL21-54	3	393.3	397.1	3.8	3.2	0.73
GL21-55	1	91.8	94.0	2.2	1.8	0.51
GL21-56	1	273.0	276.0	3.0	2.4	1.08
GL21-56	2	386.6	390.8	4.2	3.4	0.98

Hole number	Intersection		Downhole length		True thickness		Au g/t
	#	From (m)	To (m)	(m)	(m)	(m)	
GL21-57	1	319.1	323.7	4.6	3.8	0.43	
GL21-58	1	113.0	115.0	2.0	1.6	1.06	
GL21-59	1	259.7	262.0	2.3	1.8	1.14	
GL21-60	1	194.5	196.5	2.0	1.7	0.63	
GL21-61	1	87.3	117.0	29.7	24.1	1.03	
GL21-61	2	152.0	154.8	2.8	2.3	0.58	
GL21-62	1	12.0	16.0	4.0	3.3	0.77	
GL21-63	1	140.5	148.3	7.8	6.3	0.50	
GL21-63	2	181.5	198.5	17.0	13.9	0.96	
GL21-64	1	19.5	23.0	3.5	2.8	0.54	
GL21-64	2	64.5	67.9	3.4	2.7	1.76	
GL21-64	3	291.4	295.8	4.4	3.6	1.58	
GL21-64	4	442.0	451.0	9.0	7.6	1.08	
GL21-65	1	96.9	97.8	0.9	0.7	1.54	
GL21-66	1	144.2	147.7	3.5	2.9	1.51	
GL21-66	2	566.0	567.9	1.9	1.7	14.28	
GL21-66	3	594.6	597.6	3.0	2.6	0.76	
GL21-67	1	638.5	653.0	14.5	12.6	3.04	
GL21-68	1	127.3	130.3	3.0	2.4	0.96	
GL21-68	2	513.0	540.0	10.6	8.9	0.97	
GL21-69	1	89.7	94.1	4.4	3.6	1.44	
GL21-69	2	113.3	116.3	3.0	2.4	0.60	
GL21-69	3	300.4	317.0	16.6	13.5	0.73	
GL21-69	4	324.0	329.3	5.3	4.4	16.36	
GL21-69	5	339.1	365.0	25.9	21.6	1.32	
GL21-69	6	374.0	388.0	14.0	11.8	0.83	
GL21-70	1	112.0	123.2	11.2	9.3	0.55	
GL21-70	2	542.0	550.9	8.9	7.8	1.14	

## Qualified Persons and Technical Information

Mineral resources are as defined by the Canadian Institute of Mining, Metallurgy, and Petroleum's 2014 Definition Standards for Mineral Resources & Mineral Reserves. Mineral resources are not mineral reserves and have no demonstrated economic viability. There are no mineral reserves estimated at the property at this time. There are no known legal, political, environmental, or other risks that could materially affect the potential development of the mineral resources.

The mineral resource and geological information included herein is based on information included in the technical report entitled "Technical Report on the Updated Mineral Resource Estimate for the Jubu Gold Project" dated October 5, 2020 with an effective date of July 14,

2020, and is available on the Company's website at [www.arisgold.com](http://www.arisgold.com) and under the Company's SEDAR profile at [www.sedar.com](http://www.sedar.com). The technical report was prepared by Allan Armitage, Ph.D., P.Geo. of SGS Geological Services, and Joe Campbell, B.Sc., P.Geo., Alan Sexton, M.Sc., P.Geo., and Duncan Studd, M.Sc. P.Geo. of GeoVector Management Inc, each of whom are independent of the Company within the meaning of NI 43-101 and are Qualified Persons as defined by National Instrument 43-101. Messrs. Armitage, Campbell, Sexton, and Studd have reviewed and verified the drilling, sampling, assaying, and QAQC protocols and results, and are of the opinion that the sample recovery, preparation, analyses, and security protocols used for the mineral resource estimate are reliable for that purpose.

All holes drilled during 2021 were NQ diameter diamond holes completed by RJLL Drilling of Rouyn-Noranda, Quebec. GeoVector provided geological and geotechnical logging services, and sample preparation and analyses were completed by ALS Global of Sudbury, Ontario. Drill core samples were cut in half with a diamond saw and one half of the core was placed in a sample bag with a sample tag. GeoVector inserted certified standard and blank samples every tenth sample for quality assurance / quality control (QAQC) purposes. No issues were noted in the QAQC results. The sample bags were zip tied shut and placed with other sample bags in larger bags and zip tied shut. The large bags were placed on a pallet and trucked to Manitoulin Transport of New Liskeard, Ontario, and from there to ALS Global of Sudbury, Ontario. At the laboratory the sample was crushed to 70% passing 2 mm and a 250 gram subsample was taken using a riffle splitter. The subsample was pulverized to 85% passing 75 microns. A 30 gram pulverized sub-sample was assayed for gold by fire assay with atomic absorption spectroscopy. Any sample with an assay greater than 10 g/t Au was re-assayed by fire assay with gravimetric finish on a 30 gram sample.

Pamela De Mark, P.Geo., Vice President Exploration of Aris Gold is a Qualified Person as defined by National Instrument 43-101, and has reviewed and verified the drilling, sampling, assaying, and QAQC protocols and results, and is of the opinion that the drilling, sampling, sample recovery, preparation, analyses, and security protocols for the drilling program are reliable. Ms. De Mark has reviewed and approved the technical information contained herein.